

WHAT IS CLAIMED IS:

1. An improvement on a suitcase lock, comprising  
a primary lock unit fitted on a suitcase; the primary lock unit having a  
5        plurality of lock holes for securing a pair of zipper slides of the  
         suitcase in position after the slides are inserted in the holes; and  
an auxiliary unit; the auxiliary unit including:  
(1) a wire storage housing securely fitted to the suitcase; the housing  
      having an opening;  
10       (2) a reel and elastic element combination arranged in the wire storage  
         housing; and  
(3) a wire connected with a male locking tab at a first end, and the reel  
      at a second end; the wire being passed through the opening of the  
      wire storage housing at the first end thereof;  
15       the reel being biased towards a storing position by the elastic element,  
         in which storing position the wire is substantially completely  
         wound around the reel except for the first end thereof;  
the male locking tab being shaped in such a way as to be capable of  
      being secured in position by the primary lock unit when it is  
20       inserted in one of the lock holes.
2. The suitcase lock as claimed in claim 1, wherein the wire storage  
housing is secured to an inner side of the suitcase, and the first end of  
the wire is passed through a though hole of the suitcase.

3. The suitcase lock as claimed in claim 1, wherein the a stopping block  
is secured to the wire storage housing, and a control block is movably  
fitted on the storage housing with a pressing plate joined thereto; the  
wire being capable of being firmly and tightly held between the  
5 pressing plate and the stopping block to be unmovable by the reel  
when the control block is moved to a securing position.

10

15

20

25